CATALOG DOCUMENTATION NATIONAL COASTAL ASSESSMENT- NORTHEAST DATABASE YEAR 2001 STATIONS

WATER QUALITY - PHYSICAL DATA: "WATRPHYS"

TABLE OF CONTENTS

- 1. DATASET IDENTIFICATION
- 2. INVESTIGATOR INFORMATION
- 3. DATASET ABSTRACT
- 4. OBJECTIVES AND INTRODUCTION
- 5. DATA ACQUISITION AND PROCESSING METHODS
- 6. DATA MANIPULATIONS
- 7. DATA DESCRIPTION
- 8. GEOGRAPHIC AND SPATIAL INFORMATION
- 9. QUALITY CONTROL AND QUALITY ASSURANCE
- 10. DATA ACCESS AND DISTRIBUTION
- 11. REFERENCES
- 12. TABLE OF ACRONYMS
- 13. PERSONNEL INFORMATION

1. DATASET IDENTIFICATION

- 1.1 Title of Catalog document
 National Coastal Assessment-Northeast Region Database
 Year 2001 Stations
 Water Quality Physical Data
- 1.2 Authors of the Catalog entry
 John Kiddon, U.S. EPA NHEERL-AED
 Harry Buffum, CSC
- 1.3 Catalog revision date
 October 2003
- 1.4 Dataset name WATRPHYS
- 1.5 Task Group
 National Coastal Assessment-Northeast
- 1.6 Dataset identification code
 003
- 1.7 Version 001
- 1.8 Request for Acknowledgment

EMAP requests that all individuals who download EMAP data acknowledge the source of these data in any reports, papers, or presentations. If you publish these data, please include a statement similar to: "Some or all of the data described in this article were produced by the U. S. Environmental

Protection Agency through its Environmental Monitoring and Assessment Program (EMAP)".

- 2. INVESTIGATOR INFORMATION (for full addresses see Section 13)
 - 2.1 Principal Investigators
 Gerald Pesch, U.S. EPA NHEERL-AED
 Walter Galloway, U.S. EPA NHEERL-AED
 Donald Cobb, U.S. EPA NHEERL-AED
 - 2.2 Sample Collection Investigators Donald Cobb, U.S. EPA NHEERL-AED
 - 2.3 Sample Processing Investigators
 Not Applicable

3. DATASET ABSTRACT

3.1 Abstract of the Dataset

The WATRPHYS data file reports physical water quality parameters measured in the National Coastal Assessment during the summer of 2001. Included is information regarding dissolved oxygen, pH, conductivity, salinity, temperature and Secchi depth. Generally, all parameters were measured in both the surface and bottom layers of the water column. At some shallow stations (designated with a QACODE = WTR-A), measurements were performed at only one intermediate water depth and values reported identically in both surface-layer and bottom-layer parameters. Only data for the northeastern states (ME through DE) are included here. One record is presented per sampling event.

3.2 Keywords for the Dataset
Temperature, dissolved oxygen, pH, depth, conductivity, salinity, Secchi
depth

4. OBJECTIVES AND INTRODUCTION

4.1 Program Objective

The National Coastal Assessment (NCA) is a national monitoring and assessment program with the primary goal of providing a consistent evaluation of the estuarine condition in U.S. estuaries. It is an initiative of the Environmental Monitoring and Assessment Program (EMAP), and is a partnership of several federal and state environmental agencies, including: EPA's Regions, Office of Research and Development, and Office of Water; state environmental protection agencies in the 24 marine coastal states and Puerto Rico; and the United States Geological Survey (USGS) and the National Oceanic and Atmospheric Agency (NOAA). The five-year NCA

program was initiated in 2000, and is also known as the Coastal 2000 Program.

Stations were randomly selected using EMAP's probabilistic sampling framework and were sampled once during a summer index period (June to October). A consistent suite of indicators was used to measure conditions in the water, sediment, and in benthic and fish communities. The measured data may be used by the states to meet their reporting requirements under the Clean Water Act, Section 305(b). The data will also be used to generate a series of national reports characterizing the condition of the Nation's estuaries.

4.2 Dataset Objective

A two-year sampling design was employed for 2000-2001 NCA program in the Northeast. Analysts may therefore wish to consider the two years of data together.

The objective of the WATRPHYS data file is to report values of physical water quality parameters, measured during 2001, in the surface and bottom water layers of Northeastern U.S. estuaries

4.3 Dataset Background Discussion

This database contains data collected in 2001 from the Northeast component of the NCA, measured in the estuaries of the states Maine through Delaware. Nine federal-state cooperative agreements were formed to conduct the NCA program in Northeast U.S., as designated by the parameter ST_COOP (see Section 4.4). Samples collected by the ST_COOP were analyzed either by a national lab under contract to the EPA or by in-state labs, as designated by the parameter LABCODE (see Section 4.4).

The physical water quality parameters contained in this file include dissolved oxygen, pH, conductivity, salinity, temperature and Secchi depth. A continuous profile of these parameters (except Secchi depth) is measured with a CTD lowered and raised through the water column. Only the surface and bottom measurements are reported in this summary database; however the entire profiles are available from the Data Access Contact Persons (Section 10.3). At some shallow stations (designated with a QACODE = WTR-A), measurements were performed only at one intermediate water depth and values reported identically in both surface-layer and bottom-layer parameters.

If the Secchi disc hit the bottom, the reading may have been inaccurate (the true Secchi depth may have been deeper), and the parameter SECC_BOT is set to "1".

NCA planners provide two alternate locations for a station location in the event that the original location cannot be sampled. The parameter STA_ALT indicates whether the station location was the original site, first alternate, or second alternate—STA_ALT = "A", "B", or "C", respectively. Also refer to discussion in the STATIONS metadata file regarding use of this parameter during analysis of the data.

4.4 Summary of Dataset Parameters

 * denotes parameters that should be used as key fields when merging data files

*STATION Station name

*STAT ALT Alternate Site Coded (A, B or C)

*EVNTDATE Event date

SL TEMP Water temperature (deg. C) in the surface layer

SL SAL Salinity (ppt) in the surface layer

SL OXY Dissolved oxygen concentration (mg/L) in the surface layer

SL PH pH in the surface layer

BL TEMP Water temperature (deg. C) in the bottom layer

BL_SAL Salinity (ppt) in the bottom layer

BL OXY Dissolved oxygen concentration (mg/L) in the bottom layer

BL_PH pH in the bottom layer SECCHI D Secchi depth (meters)

SECC BOT Secchi on bottom (may indicate inaccurate measurement)

SL_DEPTH Depth at which surface measurements were measured BL_DEPTH Depth at which bottom measurements were measured

QACODE QACODE

<blank> No qualification.

WTR-A Indicates shallow stations (<2m) which were sampled only at mid-depth. Parameter values are reported identically in both the surface and bottom layer.

WTR-B Dissolved oxygen data are suspect due to QA/QC

failure during period of sampling.

5. DATA ACQUISITION AND PROCESSING METHODS

5.1 Data Acquisition

The sample collection methods used by USEPA trained field crews will be described here. Any significant variations by NCA partners are noted in Section 5.1.12. Details regarding NCA partners are reported in the STATIONS data file.

5.1.1 Sampling Objective

Obtain in situ measurements of temperature, salinity, conductivity, dissolved oxygen, pH and secchi depth in the surface and bottom layers of estuaries in Northeastern U.S. states during the 2001 NCA program.

5.1.2 Sample Collection: Methods Summary

Temperature, salinity, conductivity, dissolved oxygen, and pH were measured with a Hydrolab Datasonde or similar instrument, and water clarity was measured using a Secchi disk. The Hydrolab was lowered through the water column, and parameter values were recorded every meter for the first five meters and every two meters thereafter, including a value one meter above the bottom. Only the parameter values measured one meter below the surface and one meter above the bottom are reported in this data file. At some shallow stations (water depth less than 2m), measurements were performed at only one intermediate water depth and the values reported identically in both surface-layer and bottom-layer parameters.

5.1.3 Beginning Sampling Dates

25 June 2001

5.1.4 Ending Sampling Dates 31 October 2001

5.1.5 Sampling Platform

Samples were collected from gasoline or diesel powered boats, 18 to 133 feet in length

5.1.6 Sampling Equipment

Hydrolab DataSonde 3 multi-probe data logging units were used. The software program Procomm was used to set up and download profile logging runs to a laptop computer. A YSI dissolved oxygen meter (Model M58) was used to check the Hydrolab DO and temperature readings. Hand-held refractometers were used to QC the Hydrolab salinity measurements. A 20 cm diameter Secchi disk was used with a line marked in 0.2 m intervals.

- 5.1.7 Manufacturer of Sampling Equipment
 Data logger: Hydrolab Corp., Austin, TX.
 Dissolved Oxygen probe: YSI Inc.
- 5.1.8 Key Variables
 Not applicable

5.1.9 Sample Collection: Calibration

Calibration of the Hydrolab dissolved oxygen sensor was performed using the air calibration method as described by the manufacturer. The pH probe was calibrated using pH 7 and 10 standard buffer solutions. The salinity sensor was calibrated against a standard whose salinity was measured by a laboratory salinometer (Guildline AutoSal Model 8400) calibrated with IAPSO Standard Seawater ("Copenhagen water"). The salinity measurements were also checked in the field against a hand-held refractometer as a rough check. The YSI dissolved oxygen meters were calibrated immediately prior to each station using the water-saturated air calibration procedure recommended by the manufacturer. The refractometers were calibrated using deionized water and a higher salinity standard traceable to "Copenhagen water".

5.1.10 Sample Collection: Quality Control

Surface values of temperature, salinity and dissolved oxygen measured by the Hydrolab were routinely compared with independent measurements performed on a bucket of surface water (see Section 5.1.2). The Hydrolab values were considered acceptable if the following criteria were met: the two temperature values agree to within two degrees Celsius, salinity values agree to within three ppt, and dissolved oxygen values agree to within 0.5~mg/L. The Secchi depth values were measured by different crew members until values agreed within 0.1~meter.

5.1.11 Sample Collection: References

Strobel, C.J. 2000. Coastal 2000-Northeast Component: Field Operations Manual U. S. Environmental Protection Agency, National Health and Environmental Effects Research Laboratory, Atlantic Ecology Division,

Narragansett, RI. EPA/620/R-00/002.

5.1.12 Sample Collection: Alternate Methods Consult the STATIONS data file for cooperative agreement code (ST_COOP) The different partners used the following equipment:

ST COOP Water Profile Equipment СТ Sea-bird SBE-19 Sea-bird SBE-19 CT-FSH DE Hydrolab Datasonde Hydrolab Datasonde; Quanta MA MA-FSH Hydrolab Datasonde Hydrolab Datasonde ΜE NΗ YSI model 6600 M NJ-C Hydrolab Datasonde NJ-DB Hydrolab Datasonde NΥ YSI model 6600 M; YSI 85; Seabird model 25 RΙ Hydrolab Datasonde RI-FSH Hydrolab Datasonde

For ST_COOP=CT (Connecticut, Long Island Sound) and CT-FSH (Connecticut, LIS Fish Survey): no pH or Secchi depth measurements were performed.

- 5.2 Data Preparation and Sample Processing
 No analytical processing was involved for the WATRPHYS parameters.
 - 5.2.1 Sample Processing Objective
 Not applicable
 - 5.2.2 Sample Processing: Methods Summary Not applicable
 - 5.2.3 Sample Processing: Calibration
 Not applicable
 - 5.2.4 Sample Processing: Quality Control
 Not applicable
 - 5.2.5 Sample Processing: References Not applicable
 - 5.2.6 Sample Processing: Alternate Methods Not applicable
- 6. DATA ANALYSIS AND MANIPULATIONS
 - 6.1 Name of New or Modified Value
 Surface and Bottom Measurements

6.2 Data Manipulation Description

Surface and bottom measurements were extracted from continuous water profile data files by (1) sorting all records from the same water profile by depth; (2) selecting the first (minimum depth) record for all surface values; (3) selecting the last (maximum depth) for all bottom measures

7. DATA DESCRIPTION

7.1 Description of Parameters

7.1.1 Components of the Dataset

SL_DEPTH	NUM	8	Depth of Surface Measurements (m)
STATION	Char	10	Station Name
STAT_ALT	Char	1	Alternate Site Code (A, B, or C)
EVNTDATE	Num	8	Event Date
SL_TEMP	Num	8	Surface Temperature (deg. C)
SL_SAL	Num	8	Surface Salinity (ppt)
SL_OXY	Num	8	Surface Dissolved Oxygen (mg/L)
SL_PH	Num	8	Surface Layer-pH (pH units)
BL_TEMP	Num	8	Bottom Temperature (deg. C)
BL_SAL	Num	8	Bottom Salinity (ppt)
BL_OXY	Num	8	Bottom Dissolved Oxygen (mg/L)
BL_PH	Num	8	Bottom Layer-pH (pH units)
SECCHI_D	Num	8	Secchi Depth (m)
SECC_BOT	Num	8	Secchi on Bottom $(1 = yes)$
SL_DEPTH	NUM	8	Depth of Surface Measurements (m)
BL_DEPTH	NUM	8	Depth of Bottom Measurements (m)
QACODE	Char	5	QA Qualifier

7.1.2 Precision of Reported Values

The values are accurate to no more than three significant digits; however more significant digits may be reported in the dataset because of formatting restrictions.

PARAMETER	PRECISION	MIN	MAX	UNITS
SECCHI_D	0.1	0.1	9.5	meter
SL_TEMP	0.01	11.5	30.2	deg C
SL_SAL	0.01	0.01	34.2	ppt
SL_OXY	0.01	2.43	16.4	mg/L
SL_PH	0.01	3.11	9.20	pH unit
BL_TEMP	0.01	5.61	30.2	deg C
BL_SAL	0.01	0.01	34.2	ppt
BL_OXY	0.01	-0.02	14.8	mg/L
BL_PH	0.01	3.14	8.50	pH unit
SL_DEPTH	0.1	0.1	2.4	meter
SL_DEPTH	0.1	0.1	42.0	meter

- 7.1.3 Minimum Value in Dataset See Section 7.1.2
- 7.1.4 Maximum Value in Dataset See Section 7.1.2
- 7.2 Data Record Example
 - 7.2.1 Column Names for Example Records

STATION STAT_ALT EVNTDATE SL_TEMP SL_SAL SL_OXY SL_PH BL_TEMP BL_SAL BL_OXY BL_PH SECCHI_D SECC_BOT QACODE

7.2.2 Example Data Records

STATION	STAT_AI	T EVNTDATE	SL_TEMP	SL_SAL	SL_OXY	SL_PH
DE01-0012	A	9/20/01	21.7	30.1	5.7	7.7
DE01-0014	A	10/1/01	17.86	0.1	10.11	7.08
DE01-0016	A	9/19/01	21.6	20.3	6.5	7.7
DE01-0018	A	9/19/01	21.1	27.5	10.94	8.05
DE01-0020	A	9/20/01	20.94	30.76	6.37	7.86
DE01-0022	A	10/1/01	16.32	0.05	9.47	7.24

BL_TEMP	BL_SAL	BL_OXY	BL_PH	SECCHI_D	SECC_BO'	T QACODE
21.7	30.1	5.7	7.7	0.6	1	WTR-A
17.86	0.1	10.09	7.13	0.8		
21.3	20.2	6.4	7.7	0.7		
21.1	27.5	10.95	8.05	0.5	1	WTR-A
20.94	30.76	6.36	7.87	1.3	1	
16.28	0.05	9.37	7.14	0.8		

8. GEOGRAPHIC AND SPATIAL INFORMATION

- 8.1 Minimum Longitude (Westernmost) -75.6977 decimal degrees
- 8.2 Maximum Longitude (Easternmost) -67.0482 decimal degrees
- 8.3 Minimum Latitude (Southernmost)
 38.4739 decimal degrees
- 8.4 Maximum Latitude (Northernmost)
 45.1848 decimal degrees
- 8.5 Name of area or region

The National Coastal Assessment Northeast Region covers the northeastern US coastline from Maine to Delaware.

- 9. QUALITY CONTROL AND QUALITY ASSURANCE
 - 9.1 Measurement Quality Objectives
 The measurement quality objectives of the EMAP-Estuaries program specify accuracy and precision requirements of 10% in the water physical parameters. Reference: U.S. EPA. 2001. Environmental Monitoring and Assessment Program (EMAP): National Coastal Assessment Quality Assurance Project Plan 2001-2004. U.S. Environmental Protection Agency, Office of Research and Development, National Health and Environmental Effects Research Laboratory, Gulf Ecology Division, Gulf Breeze, FL. EPA/620/R-01/002. 189 p.
 - 9.2 Data Quality Assurance Procedures

 The data were reviewed to assure consistency among partners regarding sampling procedures, reporting format, etc. All measurements were performed in the field.
 - 9.3 Actual Measurement Quality
 No field replicates were measured for these parameters
- 10. DATA ACCESS
- 10.1 Data Access Procedures
 Data can be downloaded from the web
 http://www.epa.gov/emap/nca/html/regions/index.html
 - 10.2 Data Access Restrictions
 None
 - 10.3 Data Access Contact Persons
 John Kiddon, U.S. EPA NHEERL-AED, Narragansett, RI
 401-782-3034, 401-782-3030 (FAX), kiddon.john@epa.gov

Harry Buffum, Data Manager, CSC, Narragansett, RI 401-782-3183, 401-782-3030 (FAX), buffum.harry@epa.gov

- 10.4 Dataset Format
 ASCII (CSV) and SAS Export files
- 10.5 Information Concerning Anonymous FTP
 Not available
- 10.6 Information Concerning WWW
 No gopher access, see Section 10.1 for WWW access
- 10.7 EMAP CD-ROM Containing the Dataset
 Data not available on CD-ROM

11. REFERENCES

Strobel, C.J. 2000. Environmental Monitoring and Assessment Program: Coastal 2000 - Northeast component: field operations manual. Narragansett (RI): U.S. Environmental Protection Agency, National Health and Environmental Effects Research Laboratory, Atlantic Ecology Division. EPA/620/R-00/002. 68 p.

U.S. EPA. 2001. National Coastal Assessment: Field Operations Manual. U.S. Environmental Protection Agency, Office of Research and Development, National Health and Environmental Effects Research Laboratory, Gulf Ecology Division, Gulf Breeze, FL. EPA/620/R-01/003. 72 p.

U.S. EPA. 2001. Environmental Monitoring and Assessment Program (EMAP): National Coastal Assessment Quality Assurance Project Plan 2001-2004. U.S. Environmental Protection Agency, Office of Research and Development, National Health and Environmental Effects Research Laboratory, Gulf Ecology Division, Gulf Breeze, FL. EPA/620/R-01/002. 189 p.

12. TABLE OF ACRONYMS

AED Atlantic Ecology Division

CSC Computer Sciences Corporation

deg C degrees Centigrade

EMAP Environmental Monitoring and Assessment Program

EPA Environmental Protection Agency

mg/L Milligram per Liter

NCA National Coastal Assessment

NHEERL National Health and Environmental Effects Research Laboratory

ppt parts per thousand

QA/QC Quality Assurance/Quality Control

WWW World Wide Web

13. PERSONNEL INFORMATION

Sandra Benyi, Research Biologist
U.S. Environmental Protection Agency, NHEERL-AED
27 Tarzwell Drive, Narragansett, RI 02882-1197
401-782-3041, 401-782-3030 (FAX), benyi.sandra@epa.gov

Harry Buffum, Database Manager, Computer Sciences Corporation. U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3183, 401-782-3030 (FAX), buffum.harry@epa.gov

Don Cobb, Chemist

U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-9616, 401-782-3030 (FAX), cobb.donald@epa.gov

Walter Galloway, NCA Project Officer
U.S. Environmental Protection Agency, NHEERL-AED

27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3096, 401-782-3030 (FAX), galloway.walt@epa.gov

Steve Hale, EMAP Information Manager
U.S. Environmental Protection Agency, NHEERL-AED
27 Tarzwell Drive, Narragansett, RI 02882-1197
401-782-3048, 401-782-3030 (FAX), hale.stephen@epa.gov

Melissa Hughes, Data Librarian, Computer Sciences Corporation. U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3184, 401-782-3030 (FAX), hughes.melissa@epa.gov

John Kiddon, AED Oceanographer
U.S. Environmental Protection Agency, NHEERL-AED
27 Tarzwell Drive, Narragansett, RI 02882-1197
401-782-3044, 401-782-3030 (FAX), kiddon.john@epa.gov

Joe LiVolsi, AED QA Officer
U.S. Environmental Protection Agency, NHEERL-AED
27 Tarzwell Drive, Narragansett, RI 02882-1197
401-782-3163, 401-782-3030 (FAX), livolsi.joseph@epa.gov

Gerald Pesch, Director Northeast NCA and Project Officer U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3007, 401-782-3030 (FAX), pesch.gerald@epa.gov

Charlie Strobel, AED Analyst
U.S. Environmental Protection Agency, NHEERL-AED
27 Tarzwell Drive, Narragansett, RI 02882-1197
401-782-3180, 401-782-3030 (FAX), strobel.charles@epa.gov

Hal Walker, AED Analyst
U.S. Environmental Protection Agency, NHEERL-AED
27 Tarzwell Drive, Narragansett, RI 02882-1197
401-782-3134, 401-782-3030 (FAX), walker.henry@epa.gov